HYUNDAI MIGHTY EX6 Cargo/Flat Deck

Engine		
Type		Turbo Charger Intercooler
_ **		4 stroke-cycle, water-cooled, Direct-Injection Diesel engine 4 in-line
Number of Cylinder Piston Displacement (cc)		3.933
Max. Power (ps/rpm)	Euro V	140/2,500 (102 kW)
Max. Torque (lb ft/rpm)	Euro V	289/1,400 (392 nm)
Fuel System	Injection pump	Denso Common rail system
	Governor	Electrical type (ECU Control)
Transmission		
Type		5 Speed
Rear Axle		Full floating type
Type Capacity	kg	4,700
Сараску	Type	Single Reduction, Hypoid gear
Final Reduction Gear	G/Ratio	4.625
Front Axle	e/rtatio	1.020
Туре		Reverse Elliot type "I" beam
Capacity	kg	2,760
Tyre & Wheel		
Туре		Single Front, Dual Rear
Tyre	Front / Rear	205/75R17.5-10PR)
Wheel	Front / Rear	17.5 x 6.00
Steering		
Type		4-spoke, Ball-nut type, Tilt & Telescopic steering column
Steering Service Project		Power assisted
Service Brake Front / Rear		Disc / Disc
Actuation		Hydraulic with vacuum servo assistance, dual circuit
Size (mm)	Front / Rear	Disc 107 x 21.5mm
· · ·	TTOTIC TROUT	Vehicle Dynamic Control, Electronic Stability Control,
VDC		Hill Start Assistance
Parking Brake		
Actuation		Internal expanding type on propeller shaft at the rear of
Actuation		transmission assy
Size (mm) Drum diameter x Lining width x Lining thickness		ø180 x 35 x 5 (m*S5 T/M) Drum diameter x Lining width x
<u> </u>		Lining thickness
Total lining area Exhaust Brake		132 (m*S5 T/M)
Type		Vacuum operated, butterfly valve type
Suspension		racam operator, success, states type
Туре	Front / Rear	Semi-elliptic, laminated leaf springs
Spring Size (Length x Width x Thickness-	Front	1,200 x 70 x 10t-4, 11t-1
number of leaves)	Rear / Main	1,250 x 70 x 10t-4, 11t-1
<u> </u>	Rear / Helper	990 x 70 x 17t-2
Shock absorber		Air double acting telescopic type on the FRONT/REAR axle
Exhaust system		Comment of the size of the North Comment of the State of
General Toll pine		Conventional (horizontal) type muffler
Tail pipe Fuel tank		Droptail type, blowing to chassis rearward
Fuel tank Capacity		1000
Frame		
		"H" type frame with channel sectional side rail & cross
Туре		members, side rail is reinforced with outer stiffeners
Main section side rail dimension (mm)		Depth x Flange x Thickness 183 x 60 x 6t
Weights	1	
*Cargo/Flat Deck Weight kg	Unladen	3600
** May Cross Valais 14/-1-1-	Front / Rear	1940-1660
** Max Gross Vehicle Weight Gross vehicle weight	Front / Regr	5,995/6,500 2700/4700



Towing	Braked	3500
GCM (Gross Combined Mass)	Max	9495/10 000
Electrical system		
Audio		T800 (Radio+Aux+CDP/MP3+USB/IPOD) Multidisplay
Locking		Central Door Locking + Power Window + Keyless Entry +
		Semi Trim
Head lamps		Semi-sealed Beam
Front combination lamps		Turn signal / Hazard-Amber, Position - White
Fog lamps		White
Rear combination lamps		Turn signal / Hazard-Amber, Tail / Stop - Red
License plate lamp		White
Service Lamp Circuit		Yes
Back-up lamp		White
Instruments		
Meter Cluster		Fixed type
Meter		Speedometer / Tachometer / Fuel gauge / Water temperature
		gauge LCD with odometer / Trip meter / Clock
Warning lamps & indicators		Brake fluid level of reservoir / Parking brake / Oil pressure /
		Battery charge / Tell-tale lights for head light high beam / Turn
		signals / Door open / Seat belt / Low fuel
Horn		Single, Electric type
Cruise control		Yes
Heating / Air conditioning (Manual)		Yes
Body / Cab		
Type Mounting		Tilt type with torsion bars, all steel welded construction with
,, , , , , , , , , , , , , , , , , , ,		safety zone design Rigid or Semi floating type
Windshield		One piece type with laminated glass, tinted upper section
Windshield Wipers		Dual electric three speed (intermittent / low / fast) wipers &
		washer
Mirrors		Wide Width Mirror - Heated
Driver's Seat		Coil Suspension, urethane foam cushioned STD trim
Passenger's seat		Bench seat, STD Trim
Bumper		Body colour
Warranty		
3 year/ 150,000km (whichever occurs first)		Manufacturer's warranty
Annotations		

1) Empty vehicle weight and curb weight shown are to 3.5% variation to allow for production tolerance.
2) Empty vehicle weight and curb weight include weight of oil, fuel, coolant and spare tire carrier & bracket, spare tire but exclude standard tool set 3) The vehicle specifications may differ per country.

* Approximate, depending on variant and specification.

** Max. GVW includes the front & rear axle loads based on the permissible tyre load, 5,995 & 6,500 variants.





HYUNDAI MIGHTY EX6 Cargo/Flat Deck











