HYUNDAI MIGHTY EX6 Box/Tail Lift

Engine		
Type		Turbo Charger Intercooler
• •		4 stroke-cycle, water-cooled, Direct-Injection Diesel Engine
Number of Cylinder		4 in-line
Piston Displacement (cc)	Euro V	3.933
Max. Power (ps/rpm) Max. Torque (lb ft/rpm)	Euro V	140/2,500 (102 kW) 289/1,400 (392 nm)
Fuel System	Injection pump	Denso Common rail system
Fuel System	Governor	Electrical type (ECU Control)
Transmission	GOVERNO	Electrical type (EGO Control)
Type		5 Speed
Rear Axle		
Type		Full floating type
Capacity	kg	4,700
	Туре	Single Reduction, Hypoid gear
Final Reduction Gear	G/Ratio	4.625
Front Axle		
Туре	T .	Reverse Elliot type "I" beam
Capacity	kg	2,760
Tyre & Wheel		Single Front Dual Boar
Type Tyre	Front / Rear	Single Front, Dual Rear 205/75R17.5-10PR)
Wheel	Front / Rear	17.5 x 6.00
Steering	Tione / Real	17.5 x 0.00
Type		4-spoke, Ball-nut type, Tilt &Telescopic steering column
Steering		Power assisted
Service Brake		
Front / Rear		Disc / Disc
Actuation		Hydraulic with vacuum servo assistance, dual circuit
Size (mm)	Front / Rear	Disc 107 x 21.5mm
VDC		Vehicle Dynamic Control, Electronic Stability Control,
-	,	Hill Start Assistance
Parking Brake		
Actuation		Internal expanding type on propeller shaft at the rear of
		transmission assy
Size (mm) Drum diameter x Lining width x Lining thickness		ø180 x 35 x 5 (m*S5 T/M) Drum diameter x Lining width x Lining thickness
Total lining area		132 (m*S5 T/M)
Exhaust Brake		132 (III 33 17W)
Type		Vacuum operated, butterfly valve type
Suspension		7
Туре	Front / Rear	Semi-elliptic, laminated leaf springs
Shock absorber		Air double acting telescopic type on the FRONT/REAR axle
Exhaust system		
General	,	Conventional (horizontal) type muffler
Tail pipe		Droptail type, blowing to chassis rearward
Fuel tank		4000
Capacity		100ℓ
Frame		"I I" type frame with channel coational side rail 9 eross
Туре		"H" type frame with channel sectional side rail & cross members, side rail is reinforced with outer stiffeners
Main section side rail dimension (mm)		Depth x Flange x Thickness 183 x 60 x 6t
Weights		Bapatini langa n milatalasa 100 n ot
*Chassis cab weight kg	Range	4120
** Max Gross Vehicle Weight		5,995/6,500
Gross vehicle weight	Front / Rear	2700/4700
Pantech Body		
Туре		2x Rows Internal load arches
**		
Hydralic tail lift/rear door		1000kg



Electrical system	
Audio	T800 (Radio+Aux+CDP/MP3+USB/IPOD) Multidisplay
Locking	Central Door Locking + Power Window + Keyless Entry +
	Semi Trim
Head lamps	Semi-sealed Beam
Front combination lamps	Turn signal / Hazard-Amber, Position - White
Fog lamps	White
Rear combination lamps	Turn signal / Hazard-Amber, Tail / Stop - Red
icense plate lamp	White
Service Lamp Circuit	Yes
Back-up lamp	White
nstruments	
Meter Cluster	Fixed type
Anton	Speedometer / Tachometer / Fuel gauge / Water temperature
Meter	gauge LCD with odometer / Trip meter / Clock
	Brake fluid level of reservoir / Parking brake / Oil pressure /
Varning lamps & indicators	Battery charge / Tell-tale lights for head light high beam / Tur
	signals / Door open / Seat belt / Low fuel
Horn	Single, Electric type
Cruise control	Yes
Heating / Air conditioning (Manual)	Yes
Body / Cab	
Sun a Manustin su	Tilt type with torsion bars, all steel welded construction with
Type Mounting	safety zone design Rigid or Semi floating type
Vindshield	One piece type with laminated glass, tinted upper section
NATIon of the State NATion of the	Dual electric three speed (intermittent / low / fast) wipers &
Vindshield Wipers	washer
Mirrors	Wide Width Mirror - Heated
Driver's Seat	Coil Suspension, urethane foam cushioned STD trim
Passenger's seat	Bench seat, STD Trim
Bumper	Body colour
Varranty	
3 year/ 150,000km (whichever occurs first)	Manufacturer's warranty

Empty vehicle weight and curb weight shown are to 3.5% variation to allow for production tolerance.
 Empty vehicle weight and curb weight include weight of oil, fuel, coolant and spare tire carrier & bracket, spare tire but exclude standard tool set
 The vehicle specifications may differ per country.

* Approximate, depending on variant and specification.

** Max. GVW includes the front & rear axle loads based on the permissible tyre load, 5,995 & 6,500 variants.





HYUNDAI MIGHTY EX6 Box/Tail Lift









